

180 DEGREE RJ 45 KEYSTONE JACKS

Cat. 6 keystone jack.



- Meet ISO/IEC 11801, TIA/EIA568C.
- Used for Wall Plate.
- Fit for wires AWG22-26.
- IDC omsertopm life 200 cycles.
- Plug insertion life 750 cycles Min.
- Dielectric strength: When applied AC 750V or DC 1000v 1 Minute between adjacent terminal NO change.
- Material:Using PC/ABS for cover, PC for module,phosphor bronze for IDC wire post.
- Cat. 6 keystone jack 180°.

Telephone jack.



Cat. 5e keystone jack.



- Meet ISO/IEC 11801, TIA/EIA568C.
- Used for Wall Plate.
- Fit for wires AWG22-26.
- IDC omsertopm life 200 cycles.
- Plug insertion life 750 cycles Min.
- Dielectric strength: When applied AC 750V or DC 1000v 1 Minute between adjacent terminal NO change.
- Material:Using PC/ABS for cover, PC for module,phosphor bronze for IDC wire post.
- Cat. 5e keystone jack 180°

Cat. 5e keystone jack shielded.



- Meet ISO/IEC 11801, TIA/EIA568C.
- Half shielded.
- Cat. 5e 180° Half Shielded.
- Color: Black.

Telephone jack.



- For voice system.
- Contact with gold plated
- Fit for wires AWG22-26.

Part No.	Item Description
M5EU180	CAT 5e KEYSTONE JACK UNSHIELDED RJ45 180 DEGREE
M06U180	CAT 6 KEYSTONE JACK UNSHIELDED RJ45 180 DEGREE
M6AU180	CAT 6A KEYSTONE JACK UNSHIELDED RJ45 180 DEGREE