



Standard

- Electrical performance guaranteed to meet or exceed ANSI/TIA-568B Category 6 and ISO/EIC specifications.
- Independently tested and varified intertek(ETL).
- Ideal for Data center architectural requirements.
- Stranded cable for maximum flexibility.
- Available with different plug mold.
- Available with different color of cable.
- Available with different length.

Conductor

Conductor	Stranded Bare Copper 24AWG
Insulation	HDPE
Total number of insulated conductors	8, twisted in 4 pairs
Color code	White-Blue/Blue, White-Orange/Orange White-Green/Green, White-Brown/Brown
Individual pair shield	None
Overall shield	None
Drain wire	None

Nominal Transmission Characteristics

Res.	Length	Prop. Delay	Delay Skew	Freq.	Insertion Loss	NEXT	RL	ACR-N	ACR-F	PS NEXT	PS ACR-N	PS ACR-F
Ω	Max.	ns	ns	MHz	dB	dB	dB	dB	dB	dB	dB	dB
i	100m	555	50	1	3	65.0	19.0	62.0	63.3	62.0	59.0	60.3
				4	4	63.0	19.0	59.0	51.2	60.5	56.5	48.2
				8	5.7	58.2	19.0	52.5	45.2	55.6	49.9	42.2
				10	6.3	56.6	19.0	50.2	43.3	54.0	47.7	40.3
				16	8	53.2	18.0	45.2	39.2	50.6	42.6	36.2
				20	9	51.6	17.5	42.6	37.2	49.0	39.9	34.2
				25	10.1	50.0	17.0	39.9	35.3	47.3	37.2	32.3
				31.25	11.4	48.4	16.5	37.0	33.4	45.7	34.3	30.4
				62.5	16.5	43.4	14.0	26.9	27.3	40.6	24.1	24.3
				100	21.3	39.9	12.0	18.6	23.3	37.1	15.8	20.3
				200	31.5	34.8	9.0	3.3	17.2	31.9	0.3	14.2
				250	35.9	33.1	8.0	-2.8	15.3	30.2	-5.8	12.3

Part No. Legend

Patch Cord	Category	Shield	Jacket	Length	Color Code
PC	6	UTP	1 - PVC	1 MTR - 01	GREY (GY) BLUE (BU) RED (RD)
			2 - PE	2 MTR - 02	YELLOW (YL) WHITE (WH) GREEN (GR)
			3 - LSZH	Increase by every one meter	ORANGE (OR) BLACK (BL) PURPLE (PL)

Part No.	Item Description
PC06U101GY	PATCH CORD CAT 6 UTP 1 METER GREY
PC06U301GY	PATCH CORD CAT 6 UTP LSZH 1 METER GREY