

Features

- Low Insertion Loss
- Compliant with Telcordia GR-326-core, IEC, TIA
- High Precision of Mechanical Dimensions
- RoHS Compliance
- Available Ceramic or PB Sleeves
- Available Hybrid Adaptors/Shutter Adaptor

Applications

- CATV System
- Local Area Networks
- Telecommunication Networks
- FITH and FTTx
- Testing Equipments
- Fiber LAN



Specifications

Optical Parameter	W/Japanese Ceramic Sleeve	W/ Chinese Ceramic Sleeve	W/ P.B Sleeve
Insertion Loss	<0.10dB	<0.20dB	<0.30dB
Durability	<0.10dB typical change, 1000 times	<0.20dB typical change, 1000 times	<0.10dB typical change, 500 times
Operating Temp.	-20 ~+ 75 degree Celsius		
Storage Temp.	-40 ~+ 85 degree Celsius		

Part No. Legend

A/AS Adaptor	00 Connector		- 0 Simplex/Duplex		- 000 Type	
A Standard Adaptor	FC	FC	Simplex	S	Ceramic Sleeve	C
	LC	LC	Duplex	D	Phosphor Bronze	PB
	SC	SC				
	ST	ST				
B Shutter Adaptor	E2000	E2000				
	MTRJ	MJ				
	SC/APC	SCA				
	LC/APC	LCA				

Example : A-LCAD-C---Single Mode LC/APC duplex adaptor
 A-SCAS-C---Single Mode SC/APC Simplex adaptor