

This box is used as a termination point for the feeder cable to connect with drop cable in FTTH communication network systems.

It integrate fiber splicing, splitting, distribution, storage and cable connection in one unit. Meanwhile, it provides solid protection and management for the FTTH network building.



Features

- Total enclosed structure.
- Material: ABS, Wet-proof, Water-proof, Dust-proof, Anti-aging, protection level up to IP65.
- Clamping for feeder cable and drop cable, fiber splicing, fixation, storage distribution etc.
- Cable, Pigtailed, Patch cords are running through own patch without disturbing each other.
- Distribution panel can be flipped up, feeder cable can be placed in a cup-joint way which is easy for maintenance and installation.
- Box can be installed by wall mounted or pole mounted.
- Suitable for both indoor and outdoor purposes.

Mechanical Characteristics

Body Type	Dimensions	Splice trays	Capacity	Weight	In & Out
Strengthen ABS	270x350x120 mm	Splice 24 fibers	24 pcs of SC (Max)	2.10 kg	3 in and 4 out

Applications

- Wall mounting and pole mounting installation.
- FTTH pre-installation and filed installation.
- 4-7mm cable ports suitable for 2x3mm indoor FTTH drop cable and outdoor figure 8 FTTH Self-supporting drop cable.